

MUSSELWHITE - DRILL RESULTS

Hole No.	Zone	From (m)	To (m)	Drilled Width (m)	True Width (m)	Au g/t
16-WEL-084	SAD-N	159.6	162.0	2.4	1.8	2.45
16-WEL-086	SAD-N	153.4	154.0	0.6	0.5	6.14
16-WEL-088	SAD-N	143.8	158.3	14.5	14.3	4.44
16-WEL-090	SAD-N	144.5	146.1	1.6	1.6	4.98
16-WEL-084	BAN	354.7	359.0	4.3	3.7	3.59
16-WEL-089	BAN	251.5	257.0	5.5	5.4	6.32
16-WEL-086	REV	169.5	171.0	1.5	1.3	6.82
16-WEL-087	REV	162.2	170.0	7.8	7.6	10.03
16-WEL-088	REV	165.9	170.0	4.1	4.0	2.35
16-WEL-089	REV	162.0	166.5	4.5	4.4	8.45
16-WEL-089	SPR-W	107.0	109.0	2.0	1.8	2.71
16-WEL-114	SAD-N	180.0	180.6	0.6	0.5	30.00
16-WEL-115	SAD-N	142.1	147.0	4.9	4.7	7.91
16-WEL-116	SAD-N	159.3	161.1	1.8	1.7	4.01
16-WEL-117	SAD-N	145.0	147.9	2.9	2.9	2.45
16-WEL-115	REV	172.6	176.6	4.0	3.8	4.03
16-WEL-116	REV	166.4	170.0	3.6	3.1	6.69
16-WEL-117	REV	152.1	153.2	1.1	1.0	12.06
16-WEL-117	SPR	93.0	104.8	11.8	11.3	3.11
16-WEL-119	SPR	116.0	117.6	1.6	1.1	11.45
16-WEL-115	SPR-E	72.0	73.0	1.0	1.0	4.05
16-WEL-117	SPR-E	78.0	80.0	2.0	1.7	3.38
16-WEL-116	SPR-W	90.0	96.0	6.0	5.8	3.95
16-WEL-117	SPR-W	116.9	119.0	2.1	1.8	10.43
16-PQE-045	CBLOCK	180.2	183.5	3.3	3.0	12.96
16-PQE-046	CBLOCK	171.0	185.6	14.6	13.6	10.50
16-PQE-047	CBLOCK	168.0	178.0	10.0	9.7	13.54
16-PQE-048	CBLOCK	169.2	172.9	3.7	3.4	3.15
16-PQE-049	CBLOCK	162.3	167.3	5.0	5.0	3.81
16-PQE-050	CBLOCK	154.7	162.5	7.8	5.0	6.92
16-PQE-051	CBLOCK	152.5	162.0	9.5	9.4	4.65
16-PQE-052	CBLOCK	162.2	163.0	0.8	0.8	2.00
16-PQE-056	CBLOCK	175.0	178.0	3.0	2.9	7.61
16-PQE-057	CBLOCK	167.0	183.9	16.9	16.9	7.34
16-PQE-059	CBLOCK	166.2	171.0	4.8	4.4	5.03
16-PQE-060	CBLOCK	160.0	163.8	3.8	3.7	4.28
16-PQE-061	CBLOCK	152.4	156.4	4.0	4.0	6.80
16-PQE-062	CBLOCK	155.3	159.4	4.1	4.0	5.73
16-PQE-063	CBLOCK	158.6	161.0	2.4	2.3	2.26
16-PQE-067	CBLOCK	165.9	182.7	16.8	16.3	11.53

Footnotes:

- 1 All gold values are uncut.
- 2 True widths are estimated based on drill angle and interpreted geometry of mineralization.
All samples were submitted for analysis to Activation Laboratories in Dryden, Ontario, Canada.
- 3 All samples were analyzed using a 30g charge fire assay with AA finish. Samples over 10ppm gold were reanalyzed using gravimetric finish.
One in 20 samples was blank and one in 20 samples was certified reference material.
- 4 Katie Lucas, P.Geo, Exploration Manager, Musselwhite, is the Qualified Person responsible for the Musselwhite Exploration program.
- 5 Data is for the quarter ended December 31, 2016